

The L01 Location Anchor, a BLE technology based and impressive battery life beacon, is ideal for wayfinding solution, proximity marketing and asset tracking in hospital, shopping mall and warehouse.

Not only providing location-based infrastructure, it can be also integrated with temperature, humidity and barometer sensor through its hardware compatible design, to realize condition monitoring and offer comprehensive application scenarios.

What Impressed



Rotating replaceable battery



Multiple adaptive installation







IP67 waterproof



High accurancy



Historical data



Rotating replaceable



All-in-one sensor

General Specs

Contra Cpcc	•
Connectivity:	BLE 5.0
Dimensions:	76.2*53.6*24.0mm (L01)
	Ф54.5*24.0mm (L01A)
Color:	Gray
Material:	PC
IP rating:	IP67
Sensor:	Temperature&Humidity sensor
	Hall effect sensor
	Accelerometer sensor
	Barometric pressure sensor

Sensor Specs

Temperature & Humidity sensor

Accuracy tolerance:	±0.2°C(condition: 0°C - 60°C)
	±1.8% RH(condition: 20% - 80% RH)
Resolution:	0.1°C 0.1% RH
Operating temperature:	-40°C - 125°C 0 - 100 %RH
History storage:	50000 groups

Barometric Pressure Sensor

Pressure measurement range	30kPa - 125kPa
Relative pressure accuracy	±6Pa

Battery capacity:	2M Bytes
Flash memory:	2400mAh replaceable battery
Battery lifespan:	8+ years - 5s reporting
Operating temperaure:	-20°C to 60°C
	(Can be extended to -40°C~85°C)
Tramsmission range:	Up to 150m (Without any obstacles)
Installation:	Sticker Screw Zip Tie
Certification:	FCC CE RoHS REACH Bluetootl

